

12
B.S.

AD A 079606

JASON

Technical Note
JSM-79-09

December 1979

LEVEL II

SIMPLE ONE DIMENSIONAL MODELS OF THE PENETRATION OF RODS

By: Robert E. LeLievre

DDC
RECEIVED
JAN 18 1980
A

DDC FILE COPY

SRI International
1611 North Kent Street
Arlington, Virginia 22209

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited



80 1 17 053

SRI International



JASON TECHNICAL NOTE

JSN-79-09

**SIMPLE ONE DIMENSIONAL MODELS OF THE
PENETRATION OF RODS**

Robert E. LeLevier

December 1979

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER 74 SRI-JSN-79-09	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle) Simple One Dimensional Models of the Penetration of Rods,		5. TYPE OF REPORT & PERIOD COVERED Technical Note,	
7. AUTHOR(s) Robert E. LeLevier		6. PERFORMING ORG. REPORT NUMBER JSN-79-09 ✓	
9. PERFORMING ORGANIZATION NAME AND ADDRESS SRI International ✓ 1611 N. Kent Street Arlington, VA 22209		8. CONTRACT OR GRANT NUMBER(s) MDA903-78-C-0086, 150 DARPA Order-2504	
11. CONTROLLING OFFICE NAME AND ADDRESS Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS A.O. 2504, 27 & 28	
14. MONITORING AGENCY NAME & ADDRESS (if diff. from Controlling Office)		12. REPORT DATE Dec 1979	
		13. NO. OF PAGES	
		15. SECURITY CLASS. (of this report) UNCLASSIFIED	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this report) Cleared for open publication; distribution unlimited.			
17. DISTRIBUTION STATEMENT (disclaimer) The views and conclusions contained in this document are those of the author and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency or of the U.S. Government.			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) ARMOR PENETRATION LONG ROD PENETRATORS			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This note discusses a simple one dimensional model for describing the penetration of armor by rods based upon work by Alekseevshii and Gogolewski. We show that these models give incorrect results because they assume that the mass of the target material is constant, not a function of time as it actually is. We show that assuming this time dependence of the mass, yields results quite consistent with experimental data.			

389 941

mt

SIMPLE ONE DIMENSIONAL MODELS OF THE PENETRATION OF RODS

There are a large number of simple, one-dimensional models which attempt to provide estimates of the penetration of rods in target materials. Some of the models become quite sophisticated. For example, the ARAP work attempts to include the effects of target heating in the flow about the intruding projectile.

Ray Gogolewski, TTO, DARPA, discussed a particularly simple model which purported to agree essentially with the data and which provided useful scaling laws. This model is based on Alekseevshii's work^[1] and introduces the concept of mass erosion of the penetrator where u is the erosion speed in the target and is related to w , the speed of the projectile by,

$$u = \frac{w}{1 + f} \quad ,$$

where the parameter f is given by

$$f = \left(\frac{\rho_t}{\rho_p} \right)^{1/2} \quad .$$

In Equation (2), ρ_t is the target density and ρ_p , that of the penetrator.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DDC TAB	
Unannounced	
Justification	
By	
Distribution/	
Availability Codes	
Dist	Available/or special
A	

(1)

(2)

Gogolewski's model begins with the conservation of momentum written as,

$$m \frac{dv}{dt} = -\sigma_p A \quad , \quad (3)$$

Where σ_p is the yield stress of the rod, A the cross sectional area and m the mass which is decreasing with time due to erosion. This cannot be the correct momentum equation because the mass is varying with time. In the spirit of these simple models the momentum equation should read,

$$\frac{d}{dt} mv = -\sigma_p A \quad . \quad (4)$$

Let us discuss this more correct model and return to the Gogolewski approach, Eq. (3), later on.

Equation (4) is immediately integrated to give,

$$mv = m_0 v_0 \left(1 - \frac{t}{\tau}\right) \quad , \quad (5)$$

where m_0 and v_0 are the initial mass and speed of the penetrator and the time constant τ is,

$$\tau = \frac{m_0 v_0}{\sigma_p A} \quad . \quad (6)$$

The rate of mass erosion is,

$$\frac{dm}{dt} = A \rho_p (w - u)$$

$$= -A \rho_p \frac{f}{1+f} w \quad (7)$$

Eq. (7) can be integrated with the help of Eq. (5) to give,

$$m^2 = m_0^2 \left[1 - k\chi \left(1 - \frac{\chi}{2} \right) \right] \quad (8)$$

where $\chi \equiv t/\tau$ and the constant k is,

$$k = 2 \rho_p \frac{f}{1+f} \frac{w_0^2}{\sigma_p} \quad (9)$$

The penetration P is given by

$$P = \int_0^t u dt \quad (10)$$

Performing this integral we get,

$$P = L \sqrt{\frac{\rho_p}{\rho_t}} \left\{ 1 - \sqrt{1 - \frac{f}{1+f} \rho_p \frac{w_0^2}{\sigma_p}} \right\} \quad (11)$$

where L is the original length of the penetrator.

This expression for penetration leads to the result,


$$P = \frac{L}{2} \frac{\rho_p}{1+f} \frac{w_o^2}{\sigma_p} , \quad w_o^2 \ll \frac{\sigma_p}{\rho_p} , \quad (12)$$

or the penetration depth is proportional to the initial kinetic energy of the rod. This agrees with experiments in the speed domain indicated.

For very large initial speeds the mass erodes to zero before the speed of the rod goes to zero. Consequently, the penetration approaches the value,

$$P = L \sqrt{\frac{\rho_p}{\rho_t}} , \quad w_o^2 \gg \frac{\sigma_p}{\rho_p} . \quad (13)$$

This also seems to be a well known limit which agrees with experiments in the indicated speed domain. Thus we expect the penetration as a function of initial speed to look like,



in agreement with the data presented.

The crossover speed w_o^2 is given by,

$$w_o = \left(\frac{1+f}{f} \frac{\sigma_p}{P_p} \right)^{1/2} \quad (14)$$

Eqs. (11), (12) and (13) give about as much information on scaling as one can reasonably expect from such a simple one-dimensional model.

Turning to the other momentum equation (Eq. (3)), one can show that the speed w is related to the time t by,

$$\exp \left(\frac{w_o^2}{2c_o^2} \right) \exp \left(\frac{w^2}{2c_o^2} \right) dw = \frac{\sigma_p A t}{m_o} \quad (15)$$

where

$$c_o^2 = \frac{1+f}{f} \frac{\sigma_p}{P_p} \quad (16)$$

Again, if $\frac{w_o^2}{2c_o^2} \ll 1$ we find,

$$P = \frac{1}{2} L \frac{\rho_p}{1+f} \frac{w_o^2}{\sigma_p} \quad (17)$$

as before. On the other hand, as w_o increases, the penetration increases without bound which seems to contradict the data!

LIST OF REFERENCES

1

- V. P. Alekseevshii, "Penetration of a Rod into a Target at High Velocity", Fizika Goreniya i Vzvyva, Vol. II, #2, p. 99-106, (1966), UDC532.501.32

DISTRIBUTION LIST

ORGANIZATION	NO. OF COPIES	ORGANIZATION	NO. OF COPIES
Dr. Arden Bement Deputy Under Secretary of Defense for R&AT Room 3E114, The Pentagon Washington, D.C. 20301	2	Dr. Richard L. Garwin IBM, TJ Watson Research Center P.O. Box 218 Yorktown Heights, NY 10598	1
Dr. Gregory Canavan Director, Office of Inertial Fusion, U.S. DOE M.S. C404 Washington, D.C. 20545	1	Dr. Raymond P. Gogolewski DARPA 1400 Wilson Boulevard Arlington, VA 22209	1
Dr. Robert Clark P.O. Box 1925 Washington, D.C. 20013	1	Director National Security Agency Fort Meade, MD 20755 ATTN: Mr. Thomas Handel, A243	1
Cmdr. Robert Cronin NFOIO Detachment, Suitland 4301 Suitland Road Washington, D.C. 20390	1	Dr. Robert J. Hermann Assistant Secretary of the Air Force (RD&L) Room 4E856, The Pentagon Washington, D.C. 20330	1
Defense Documentation Center Cameron Station Alexandria, VA 22314	12	Dr. Benjamin Huberman Associate Director, OSTP Room 476, Old Executive Office Building Washington, D.C. 20506	1
Dr. David D. Elliott SRI International 333 Ravenswood Avenue Menlo Park, CA 94025	1	Dr. Jonathan I. Katz Department of Astronomy University of California Los Angeles, California 90024	1
Director National Security Agency Fort Meade, MD 20755 ATTN: Mr. Richard Foss, A42	2	Mr. Eugene Kopf Principal Deputy Assistant Secretary of the Air Force (RD&L) Room 4E964, The Pentagon Washington, D.C. 20330	1
Dr. Robert Fossum, Director DARPA 1400 Wilson Boulevard Arlington, VA 22209	2	Mr. Ray Leadabrand SRI International 333 Ravenswood Avenue Menlo Park, CA 94025	1
Dr. Edward A. Frieman Director, Office of Energy Research, U.S. DOE M.S. 6E084 Washington, D.C. 20585	1	Dr. Robert E. LeLevier 961 Jacon Way Pacific Palisades, CA 90272	1
Dr. George Gamota OUSDRE (R&AT) Room 3D1067, The Pentagon Washington, D.C. 20301	3		

<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>
Mr. Barry Leven NISC/Code 20 4301 Suitland Road Washington, D.C. 20390	1	Ms. Alma Spring DARPA/Administration 1400 Wilson Boulevard Arlington, VA 22209	1
Dr. Donald M. LeVine SRI International 1611 N. Kent Street Arlington, VA 22209	3	SRI/MP Reports Area G037 333 Ravenswood Avenue Menlo Park, CA 94025 ATTN: D. Leitner	2
Director National Security Agency Fort Meade, MD 20755 ATTN: Mr. Robert Madden, R/SA	2	Mark L. Wilkins Lawrence Livermore Laboratory P.O. Box 808 MC L-355 Livermore, CA 94550	1
Mr. John Meson DARPA 1400 Wilson Boulevard Arlington, VA 22209	1		
Mr. Robert Moore ODDR&E (TWP) Room 3E1044, The Pentagon Washington, D.C. 20301	1		
The Honorable William Perry Under Secretary of Defense (R&E) Office of the Secretary of Defense Room 3E1006, The Pentagon Washington, D.C. 20301	1		
Dr. Eugene Ruane P.O. Box 1925 Washington, D.C. 20013	2		
Mr. Gordon Sigman, Director Tactical Technology Office DARPA 1400 Wilson Boulevard Arlington, VA 22209	1		
Dr. Joel A. Snow Senior Technical Advisor Office of Energy Research, U.S. DOE, M.S. E084 Washington, D.C. 20585	1		